

NESS CCTV - FOR CONSISTENT COMMITMENT TO VALUE



100-367, 100-370



100-371



100-311



100-314 Optional ceiling suspension bracket.
COMPATIBLE WITH ALL PRO SERIES HOUSINGS.
Ceiling bracket and housing sold separately.



100-313 Optional Pole Mounting Bracket.
COMPATIBLE WITH ALL PRO SERIES HOUSINGS.

NESS PRO SERIES HOUSINGS

WEATHERPROOF PROFESSIONAL CAMERA HOUSINGS

Ness Pro Series housings are the ultimate high quality outdoor camera enclosures at an affordable price. All models are supplied complete with swivel bracket, grommet cable entry, prefitted internal terminal strips and fuse.

Model 100-367 has a cover which completely removes for total access to the camera. IP66 weatherproof rated, (dust tight, proof against powerful water jets).

Model 100-370 as above and also has a built-in heater/window demister for cold climates. IP66 weatherproof rated.

Model 100-371 has a rear hinged cover with hold-open latch. Features concealed cable entry and built-in heater/demister and cooling fan. IP44 weatherproof rated (Splash proof - Rain proof).

Model 100-311 side opening design allows the lid to fully swing open while remaining attached to the body. Cable entry is fully concealed and secure via the bracket supplied. IP67 weatherproof rated (dust tight, waterproof). Also features a removable full length sun hood.

POSSIBLY THE BEST ENVIRONMENTAL HOUSINGS MONEY CAN BUY! MOUNTING BRACKET INCLUDED.

| | |
|---------|--|
| 100-367 | PRO HOUSING inc wall bracket |
| 100-370 | PRO HOUSING WITH HEATER inc wall bracket |
| 100-371 | PRO HOUSING WITH HEATER/FAN inc wall bracket |
| 100-311 | PRO HOUSING SIDE OPENING inc wall bracket |
| 100-313 | POLE MOUNTING BRACKET suits all models |
| 100-314 | CEILING SUSPENSION BRACKET suits all models |

| Specifications | 100-367 | 100-370 | 100-371 | 100-311 |
|---|---------------------|-------------------|-----------------------|--------------------|
| WEATHER PROTECTION | IP66 | | IP44 | IP67 |
| HEATER | no | yes | yes | no |
| COOLING | no | no | yes | no |
| INTERNAL DIMENSIONS (W x H x L) camera capacity | 90 x 70 x 230 mm | | 105 x 80 x 300 mm | 90 x 70 x 230 mm |
| EXTERNAL DIMENSIONS (W x H x L) Body only | 127 x 124 x 390 mm | | 135 x 158 x 450 mm | 140 x 120 x 380 mm |
| INTERNAL ACCESS | Fully removable lid | | Rear hinge | Side hinge |
| OPERATING VOLTAGE | - | 24V AC for heater | 24V AC for heater/fan | - |
| CURRENT DRAW | - | 2A | 2A | - |
| WEIGHT inc bracket | 2.5kg | 2.6kg | 3.65kg | 3.1kg |

SYDNEY 02 8825 9222
sales@ness.com.au

MELBOURNE 03 9875 6400
nessmelb@ness.com.au

BRISBANE 07 3399 4910
nessbris@ness.com.au

PERTH 08 9328 2511
nessper@ness.com.au

ADELAIDE 08 8277 7255
adelaide@ness.com.au



CCTV Products

www.ness.com.au

Consistent™
Omnipresent
To
Value